

warm hearted, hand crafted

Sole Distributor:

JOVEN ELECTRIC (S) PTE LTD

No 10 Ubi Crescent, #02-18 Ubi Techpark,
Singapore 408564.

T: +65 6283 3181, 6749 6421 F: +65 6749 3575

E: jovensales@gmail.com | jovensgp@singnet.com.sg

www.jovenelectric.com

Authorised Dealer

www.jovenelectric.com



























The All New SA15m Instant Hot Shower with 10mA Extra-Safe ELCB Technology



Refreshing & Extra Safer Shower **Instant Hot Shower**



SA15 Series Instant Hot Shower Refreshing & Safer Shower



Crafted for Perfection Ultimate Relaxation

The SA15m Instant Hot Shower is what every household desired for - High Performance, Timeless Design coupled with Extra Safety Features.

With a Compact, Slim and Designer casing, your bathroom will always have a touch of contemporary, even in years to come.

Total Relaxation can only be enjoyed with Peace of Mind. Joven SA15m is equipped with Built-in Double Pole ELCB System and covered with Splash Proof Casing for Worry-Free Shower.

So, when style meets comfort to befit your lifestyle, you know that you have made the right choice in picking the Joven SA15mInstant Hot Shower.

CHROME SLIM SLIDER BAR SET




Slim and unique slider bar. Just press to set the hand shower to your ideal position.

*Chrome accessories are only available for silver colour.



it's so easy!



Wide Spray

SPRAY OPTIONS

3 ideal shower mode spray pattern can be selected just

by turning the spray selector,





INTERNAL PARTS

• 1 Year Warranty On Internal Parts



SERVICE ASSURED

- After-Sales Service Assured Door To Door
- Spare Parts Available

SPECIFICATION

Electrical Loading	2.2 kW 10.0 A 220 Va.c. 50 / 60Hz 3.3 kW 15.0 A 220 Va.c. 50 / 60Hz 3.5 kW 16.0 A 220 Va.c. 50 / 60Hz 4.4 kW 20.0 A 220 Va.c. 50 / 60Hz 4.5 kW 21.0 A 220 Va.c. 50 / 60Hz 5.2 kW 24.0 A 220 Va.c. 50 / 60Hz 5.5 kW 25.0 A 220 Va.c. 50 / 60Hz	3.0 kW 13.0 A 230 Va.c. 50Hz 3.3 kW 15.0 A 230 Va.c. 50Hz 3.6 kW 16.0 A 230 Va.c. 50 / 60Hz 4.8 kW 21.0 A 230 Va.c. 50 / 60Hz 3.6 kW 15.0 A 240 Va.c. 50 / 60Hz 5.2 kW 21.8 A 240 Va.c. 50 / 60Hz
Water Pressure	Min.: 10 kPa / 1.45 psi / 0.1 bar	Max.: 380 kPa / 55 psi / 3.8 bar
Water Flow	Min.: 2 Litres per Minute	Max.: 8 Litres per Minute
Water Temp. Control	Stepless Electronic Power Control	
Double Pole ELCB	10 mA Trip Sensitivity	
Inlet / Outlet Connection	ø15 mm (1/2" BSP) - Single Point System	
Dimensions	221 X 341 X 89 mm	

INNOVATIVE AND SAFETY FEATURES



Weight

Built-In Double Pole ELCB System

- 10mA Sensitivity
 Test / Reset Safety Functions
- Reliable Electro-mechanical



Electronic Power Control

2.50 kg

- Stepless Electronic Power Control
- Ideal Shower Temperature Energy Saving



Innovative SF Valve

- 1/4 Turn Ceramic Valve
- Stop And Control Water Volume
- Built-In Filter



Safety Thermostat / Thermal Cut-Out

- Anti Scalding
- Overheating Protection
- Against Water Splash Against Access To

Splash Proof Casing IP25

